

543,194

Rec'd PCT/PTO 21 JUL 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
7 July 2005 (07.07.2005)

PCT

(10) International Publication Number
WO 2005/061768 A1

- (51) International Patent Classification⁷: **D03D 11/00**, B65G 15/34
- (21) International Application Number: PCT/US2003/037015
- (22) International Filing Date: 18 November 2003 (18.11.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (for all designated States except US): **MOL BELTING COMPANY** [US/US]; 2532 Waldorf Court, Grand Rapids, MI 49544 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **MOL, Edward, T.** [US/US]; 12374 24th Avenue, Marne, MI 49435 (US).
- (74) Agent: **BAIR, Joel, E.**; McGarry Bair PC, 171 Monroe Ave. NW, Suite 600, Grand Rapids, MI 49503 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: INTERWOVEN BELT FABRIC



(57) **Abstract:** An interwoven belting fabric (100, 200) for use in conveyors, including treadmills, is constructed of a dual layer of weft yarns (105, 106, 206, 207) comprising adjacent couplets (110-119, 210-219), a plurality of middle warp yarns (107, 208), and a plurality of binder warp yarns (120-122, 220-222). Each middle warp yarn is heat set under tension so that it is sufficiently straight and inelastic to bear loads under tension without twisting or stretching.

WO 2005/061768 A1